## GENERAL NOTES Dimensions are from inside pool panels. |4' X 28' RECTANGLE 4' RADIUS - WEDGE ese are finished dimensions ready for the liner. 7 4'R 4'R 4<sup>'</sup>R 4'R 6' SWIMOUT (optional) -1 6' PANEL +1 6' SWIMOUT 4 o<sup>i</sup> 13 Q Q COZY COVE 2. Soil to have minimum bearing capacity of 2000 P.S.F. 3. Locate top of pool at least 6" above surrounding land elevation. 4. See 'Over Dig Detail' for excavation around pool. 5. Fill yolds under base of panels and tamp well. 6. Backfill with non-expansive material. **EXCAVATION NOTES** Rough excavation should be 2" deeper in each instance. 28 6' SWIMOUT ō ο 8' COZYCOVE (optional) -2 4' PANELS -1 BRACE +1 8' COZY COVE 4 4 4 R The dealer or contractor who sells or installs your pool is an independant contractor and is not an THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. ADDITIONAL NOTES 4'R 4 R Q **4'R COZY CORNER** +1 6' STEP -1 6' PANEL 8' STEP (optional) -1 Brace +1 4'R Cozy Step 4'R COZY CORNER (optional) 6' STEP -2 4'R panels QTY PART COPING LAYOU **G** W BILL OF MATERIALS Q HP199 BRACE HP204 HP206L | 6' PANEL (LIGHT) HP206A | 6' PANEL (A/G) HP206 | 6' PANEL HP254 | 4'R PANEL 3'4" 28 28 4 ගු 4' PANEL DESCRIPTION ഗ 3 U Z 12 12 20 4 PERIMETER œ œ -G--I-PANEL SHELF DETAIL \*NOTE: REFER TO INSTALLATION MANUAL FOR MORE INFO. Q CONCRETE BOND BEAM 6" TO 8" DEER 77'2" E NON-EXPANSIVE MATERIAL FOR — BACKFILL APPROX 4" DEEP BRACE It is your responsibility to ensure the safety package provided is delivered to the pool owner and that the "NO DIVING" labels are properly installed. ATTENTION DEALER/BUILDER: NO DIVING WARNING PRE-CUT PANEL LEGEND NO DIVING SHALLOW WATER DIVING MAY CAUSE DEATH OR PERMANENT INJURY SUGGESTED LABEL LOCATIONS ARE SPECIFIED IN THE COPING LAYOUT 'NO DIVING' WARNING LABELS MUST BE ACCORDING TO NSPI SPECIFICATIONS SQ. FOOTAGE INSTALLED IN NO DIVING AREAS HSH — 2' OVERDIG — **GALLONS** œ AQUAGENIE COPING 2' VERMICULITE OR SAND BOTTOM BENCHMARK VINYL LINER 11753 392

3. The ideal water level should be to the middle of the skimmer opening(s).

construction. Proper installation is the responsibility of the dealer/builder/contractor. only to normal ground conditions. There may be additional precautions and/or methods of agent of the Manufacturer. The construction methods illustrated here are suggestions and apply

JAN 2012 CORNERSTONE

14' X 28' RECTANGLE 4' RADIUS - WEDGE

20115-PWH