GENERAL NOTES . The ideal water level should be to the middle of the skimmer opening(s). Dimensions are from inside pool panels. 8' X 36' RECTANGLE 6" RADIUS ese are finished dimensions ready for the liner. $\overline{\infty}$ 6"R 6"R oⁱ o d ω Q ō 6' SWIMOUT Q oⁱ Q. 2. Soit to have minimum bearing capacity of 2000 P.S.F. 3. Locate top of pool at least 6" above surrounding land elevation. 4. See 'Overdig Detail' for excavation around pool. 5. Fill yords under base of panels and tamp well. 6. Backfill with non-expansive material. EXCAVATION NOTES 6' SWIMOUT (optional) -1 6' PANEL +1 6' SWIMOUT Rough excavation should be 2" deeper in each instance. Q COZY COVE ο 40'-3" ႘ၟ 4 ο ō +1 BRACE +1 8' COZY COVE 8' COZYCOVE (optional) -1 6' PANEL +2 1' PANELS -1 4' PANEL ō The dealer or contractor who sells or installs your pool is an independant contractor and is not an only to normal ground conditions. There may be additional precautions and/or methods of agent of the Manufacturer. The construction methods Illustrated here are suggestions and apply THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. ADDITIONAL NOTES ο Q Q 4 ω 6"R 6"R Q Q -2 6' PANEL +1 4' PANEL +1 8' STEP 8'STEP (optional) 4 8' STEP QTY PART COPING LAYOU **G** BILL OF MATERIALS 12' HP256 | 6"R PANEL HP204A | 4' PANEL (A/G) HP204L | 4' PANEL (LIGHT HP204 | 4' PANEL HP206 | 6' PANEL HP203 3' PANEL 4'8" 3'4" 8 ळ ą DESCRIPTION 12 12 ഗ 3 U Z 4 ರಾ 겋 12 12 PERIMETER 107'2" -G---I--10 10 OVERDIG DETAIL *NOTE: REFER TO INSTALLATION MANUAL FOR MORE INFO. 12' 4 USE NON-EXPANSIVE HATERIAL FOR BACKFILL APPROX 4" DEEP POLYMER BRACE EARTH -J--K--It is your responsibility to ensure the safety package provided is delivered to the pool owner and that the "NO DIVING" labels are properly installed. ATTENTION DEALER/BUILDER: NO DIVING WARNING PRE-CUT PANEL LEGEND NO DIVING SHALLOW WATER DIVING MAY CAUSE DEATH OR PERMANENT INJURY 'NO DIVING' WARNING LABELS MUST BE ACCORDING TO NSPI SPECIFICATIONS SUGGESTED LABEL LOCATIONS ARE SPECIFIED IN THE COPING LAYOUT SQ. FOOTAGE INSTALLED IN NO DIVING AREAS HSH -2' OVERDIG-**GALLONS** AQUAGENIE 2' VERMICULITE OR SAND BOTTOM BENCHMARK 22,133 648

construction. Proper installation is the responsibility of the dealer/builder/contractor.

JAN 2012 CORNERSTONE

18' X 36' RECTANGLE 6" RADIUS

Copyright © 2012 by Hydra Pools

20140-PWH