uvument ID: HF5100, Hydra Standard Panel Layout Drawing Rev Date: 1216/2005 Rev Level<sup>-</sup> A

JAN 2012 | CORNERSTONE

20' X 40' RECTANGLE 6" RADIUS - WEDGE

Copyright © 2012 by Hydra Pools

20161-PWH

## GENERAL NOTES 20' X 40' RECTANGLE 6" RADIUS - WEDGE . The ideal water level should be to the middle of the skimmer opening(s). Dimensions are from inside pool panels. ese are finished dimensions ready for the liner. 6"R 6"R ο Q ω 4 4 ق Q Q 6' SWIMOUT <u>ق</u> 2. Soil to have minimum bearing capacity of 2000 P.S.F. 3. Locate top of pool at least 6" above surrounding land elevation. 4. See 'Overdig Detail' for excavation around pool. 5. Fill voids under base of panets and tamp well. 6. Backfill with non-expansive material. Q Q EXCAVATION NOTES Rough excavation should be 2" deeper in each instance. COZY COVE 6' SWIMOUT (optional) -1 6' PANEL +1 6' SWIMOUT 40 ο ο 8' COZYCOVE (optional) -2 4' PANELS -1 6' PANELS +2 3' PANELS +1 8' COZY COVE Q Q ō The dealer or contractor who sells or installs your pool is an independant contractor and is not an only to normal ground conditions. There may be additional precautions and/or methods of agent of the Manufacturer. The construction methods Illustrated here are suggestions and apply THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. ADDITIONAL NOTES 出 Q Q Proper installation is the responsibility of the dealer/builder/contractor. 4 4 ω 6"R 6"R οĪ Q Q 8' STEP (optional) -3 6' PANEL +2 5' PANEL +1 8' STEP ω ហ្ម 8' STEP 27 24 COPING LAYOU **G** Þ $\boldsymbol{\varpi}$ BILL OF MATERIALS 12 ٥ HP204 HP199 | BRACE HP206L | 6' PANEL (LIGHT HP206 | 6' PANEL PART HP256 | 6"R PANEL 3'4" × 28 6 20 챵 DESCRIPTION 12 12' 木 ഗ 3 U Z <u>ფ</u> 12 12 PERIMETER 119'2" -G--I-12 12' OVERDIG DETAIL \*NOTE: REFER TO INSTALLATION MANUAL FOR MORE INFO. 12' Q CONCRETE BOND BEAM 6" TO 8" DEEP <del>⊹</del> □ E NON-EXPANSIVE MATERIAL FOR — BACKFILL APPROX 4" DEEP BRACE It is your responsibility to ensure the safety package provided is delivered to the pool owner and that the "NO DIVING" labels are properly installed. ATTENTION DEALER/BUILDER: NO DIVING WARNING PRE-CUT PANEL LEGEND NO DIVING SHALLOW WATER DIVING MAY CAUSE DEATH OR PERMANENT INJURY 'NO DIVING' WARNING LABELS MUST BE ACCORDING TO NSPI SPECIFICATIONS SUGGESTED LABEL LOCATIONS ARE SPECIFIED IN THE COPING LAYOUT INSTALLED IN NO DIVING AREAS SQ. FOOTAGE HSH --- 2' OVERDIG --**GALLONS** Ö AQUAGENIE 13 PANEL 2' VERMICULITE OR SAND BOTTOM BENCHMARK VINYL LINER 25793 800 + \*