The ideal water level should be to the middle of the skimmer opening(s). GENERAL NOTES Dimensions are from inside pool panels 6' X 41' X 24' TRUE "L" RIGHT 2' RADIUS (90°) 8' COZY COVE (optional) -2 6' PANELS +1 4' PANEL +1 8' COZY COVE ese are finished dimensions ready for the liner. 2'R 2'R 6' SWIMOUT (optional) -1 6' PANEL +1 6' SWIMOUT Q 6 ō COZY COVE ο Q 25 6' SWIMOUT 2. Soit to have minimum bearing capacity of 2000 P.S.F. 3. Locate top of pool at least 6" above surrounding land elevation. 4. See 'Overdig Detail' for excavation around pool. 5. Fill yords under base of panels and tamp well. 6. Backfill with non-expansive material. **EXCAVATION NOTES** ō Q Rough excavation should be 2" deeper in each instance. 4 4 4 4 ō σį 2'R 2 ō <u> 1</u> ο 28'-10-8' STEP 혌 ō The dealer or contractor who sells or installs your pool is an independant contractor and is not an only to normal ground conditions. There may be additional precautions and/or methods of agent of the Manufacturer. The construction methods illustrated here are suggestions and apply THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. ADDITIONAL NOTES ο 2 8' STEP (optional) -2 6' PANELS +2 2' PANELS +1 BRACE +1 8' STEP Proper installation is the responsibility of the dealer/builder/contractor. IJĴ 2'R 2'R | ہم [ف oⁱ Q 4 24 2'R CORNER STEP ω +1 2'R STEP +1 4' PANEL +1 3' PANEL -1 2'R PANEL -2 6' PANELS -1 1' PANEL -1 BRACE 2'RAD STEP (optional) QTY PART COPING LAYOUT **G** Þ W BILL OF MATERIALS 12 |HP252M| 2'R PANEL HP204 HP202 | 2' PANEL HP204L | 4' PANEL (LIGHT HP206 | 6' PANEL HP201 | 1' PANEL HP205 | 5' PANEL 48 3'4" 41 <u>6</u> ω 4' PANEL REVERSE 90° PANEL DESCRIPTION 12 12' <u>₹</u> 木 ഗ 3 U Z 25 24 1 4 ರಾ ಕ್ಕ ω_ 9'6" 12 PERIMETER 125'8" -G---I--12 12' OVERDIG DETAIL *NOTE: REFER TO INSTALLATION MANUAL FOR MORE INFO. W 12' CONCRETE BOND BEAM 6" TO 8" DEEP œ E NON-EXPANSIVE MATERIAL FOR — BACKFILL APPROX 4" DEEP BRACE -J--K--It is your responsibility to ensure the safety package provided is delivered to the pool owner and that the "NO DIVING" labels are properly installed. ATTENTION DEALER/BUILDER: NO DIVING WARNING PRE-CUT PANEL LEGEND NO DIVING SHALLOW WATER DIVING MAY CAUSE DEATH OR PERMANENT INJURY 3/8" REBAR WHERE NEEDED AROUND PERIMETER OF BOND BEAM SUGGESTED LABEL LOCATIONS ARE SPECIFIED IN THE COPING LAYOUT 'NO DIVING' WARNING LABELS MUST BE ACCORDING TO NSPI SPECIFICATIONS INSTALLED IN NO DIVING AREAS **SQ. FOOTAGE** HGHT ---2' OVERDIG ---DANGER GALLONS AQUAGENIE 13 PANEL 2' VERMICULITE OR SAND BOTTOM BENCHMARK VINYL LINER 24,228 784

20511-PWH

JAN 2012 CORNERSTONE

16' X 41' X 24' TRUE L RIGHT 2' RADIUS