uvument ID: HF5100, Hydra Standard Panel Layout Drawing Rev Date: 1216/2005 Rev Level<sup>-</sup> A

Proper installation is the responsibility of the dealer/builder/contractor.

JAN 2012 | CORNERSTONE

16' X 41' X 32' TRUE L RIGHT 4' RADIUS

Copyright © 2012 by Hydra Pools

20558-PWH

## The ideal water level should be to the middle of the skimmer opening(s). GENERAL NOTES Dimensions are from inside pool panels 6' X 41' X 32' TRUE "L" RIGHT 4' RADIUS (2'RR) ese are finished dimensions ready for the liner. 8' COZY COVE (optional) -1 6' PANEL -1 4' PANEL -1 3' PANEL -1 BRACE +1 5' PANEL +1 8' COZY COVE 혓 즁 4'R 4'R 4 R 4'R υ o j COZY COVE ٥ 25 2. Soil to have minimum bearing capacity of 2000 P.S.F. 3. Locate top of pool at least 6" above surrounding land elevation. 4. See 'Overdig Detail' for excavation around pool. 5. Fill voids under base of panets and tamp well. 6. Backfill with non-expansive material. **EXCAVATION NOTES** Rough excavation should be 2" deeper in each instance. 6' SWIMOUT Q ō $44'-0\frac{1}{4}$ 4 ω ω 6' SWIMOUT (optional) -1 6' PANEL +1 6' SWIMOUT 4'R ٥ ō 4'R Q 4 8' STEP $35'-9_{\Lambda}''$ $22'-7\frac{1}{2}"$ ô The dealer or contractor who sells or installs your pool is an independant contractor and is not an only to normal ground conditions. There may be additional precautions and/or methods of agent of the Manufacturer. The construction methods illustrated here are suggestions and apply THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. ADDITIONAL NOTES 4 4 8' STEP (optional) -2 4' PANELS -1 BRACE +1 8' STEP 4'R 4'R 4'R 4'R Q oj Q 4'R COZY CORNER ಜ್ಞ 4'R COZY STEP (optional) -2 4'R PANELS -1 BRACE +1 4'R COZY STEP QTY PART 00 COPING LAYOU **G** Þ W BILL OF MATERIALS HP252RR 2' RADIUS REVERSE HP204 | HP206A | 6' PANEL (A/G) HP254 | 4'R PANEL HP202 HP203 | 3' PANEL HP204L | 4' PANEL (LIGHT HP206 | 6' PANEL HP205 | 5' PANEL 48 3'4" 41 <u>6</u> ω 2' PANEL 4' PANEL DESCRIPTION 12 12' S 木 Z 3 U 32 7 4 ರಾ 25 ಕ್ಕ 형 12 10 PERIMETER 137'5" -G---I--ڡ œ \*NOTE: REFER TO INSTALLATION MANUAL FOR MORE INFO. OVERDIG DETAIL W 12' 12 CONCRETE BOND BEAM 6" TO 8" DEEP E NON-EXPANSIVE MATERIAL FOR — BACKFILL APPROX 4" DEEP BRACE -J--K--It is your responsibility to ensure the safety package provided is delivered to the pool owner and that the "NO DIVING" labels are properly installed. ATTENTION DEALER/BUILDER: NO DIVING WARNING PRE-CUT PANEL LEGEND NO DIVING SHALLOW WATER SHALLOW WATER INJURY 3/8" REBAR WHERE NEEDED AROUND PERIMETER OF BOND BEAM SUGGESTED LABEL LOCATIONS ARE SPECIFIED IN THE COPING LAYOUT 'NO DIVING' WARNING LABELS MUST BE ACCORDING TO NSPI SPECIFICATIONS INSTALLED IN NO DIVING AREAS SQ. FOOTAGE HSH ---2' OVERDIG ---DANGER GALLONS AQUAGENIE 101 PANEL COPING 2' VERMICULITE OR SAND BOTTOM BENCHMARK VINYL LINER 26,742 912