7'7" X 32'5" BAHAMA

Þ

17'7"

木

110 ∞_

32'43/," 3'4"

PERIMETER

86'8"

GALLONS

13,104 570

SQ. FOOTAGE

2'8"

7'31/4"

a

۷AR


S


U

-G--I-

-J--K--

LAYOUT DIMENSIONS





RAD 8' STEP

NOIE RET	YOUT	COPING LAYOUT	CO
*IOTE			
CONCRE			
UNDIS	BRACE	HP199	29
	30° LAZY-ELL PANEL	HP221	4
	HP219N 9'R REVERSE (*)	HP219N	∞
USE NON	(9'R) 1' OVAL INSERT	HP215	_
	(9'R) 3' ROMAN INSERT	HP225	ω
	HP259A 9'R PANEL (A/G)	HP259A	2
	HP259LL 9'R PANEL (LIGHT)	HP259LL	_
	9'R PANEL	HP259	∞
	6' PANEL	HP206	2
CON	DESCRIPTION	QTY PART	QTY
OVERDIG	BLLL OF MATERIALS	L OF MA	118
			1

9'R (2')

MATERIAL FOR BACKFILL BRACE NCRETE DECK 6" TO 8" DEEP 3/8" REBAR WHERE NEEDED AROUND PERIMETER OF BOND BEAM — 2' OVERDIG → PANEL 2' VERMICULITE OR SAND BOTTOM BENCHMARK VINYL LINER

9'R 9'R 9'R 9'RR ο <u>ن</u> 9'RR 9'R 9'R

It is your responsibility to ensure the safety package provided is delivered to the pool owner and that the "NO DIVING" labels are properly installed. ATTENTION DEALER/BUILDER:

FER TO INSTALLATION MANUAL FOR MORE INFO.

NO DIVING WARNING

'NO DIVING' WARNING LABELS MUST BE INSTALLED IN NO DIVING AREAS

NO DIVING
SHALLOW WATER
DIVING MAY CAUSE DEATH OR PERMANENT INJURY ACCORDING NSPI SPECIFICATIONS

SUGGESTED LABEL LOCATIONS ARE SPECIFIED IN THE COPING LAYOUT







20900-PWH

Copyright © 2012 by Hydra Pools

uocument ID: HF5100, Hydra Standard Panel Layout Drawing Rev Date: 12/6/2005 Rev Level: A

3. The ideal water level should be to the middle of the skimmer opening(s).

2. Soil to have minimum bearing capacity of 2000 P.S.F.
3. Locate top of pool at least 6" above surrounding land elevation.
4. See 'Overdig Detail' for excavation around pool.
5. Fill words under base of panets and tamp well.
6. Backfill with non-expansive material.

EXCAVATION NOTES

Rough excavation should be 2" deeper in each instance.

The dealer or contractor who sells or installs your pool is an independant contractor and is not an

THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY.

ADDITIONAL NOTES

construction. Proper installation is the responsibility of the dealer/builder/contractor. only to normal ground conditions. There may be additional precautions and/or methods of agent of the Manufacturer. The construction methods illustrated here are suggestions and apply

Dimensions are from inside pool panels.

nese are finished dimensions ready for the liner.

GENERAL NOTES

JAN 2012 CORNERSTONE

17'7" X 32'5" BAHAMA