21'8" X 35'9" LAGOON RIGHT 1-2 1-3 LAYOUT DIMENSIONS A-B 41'91/4" 18'11¼" 24'6¼" 27'81/2" 50'11/2" 19'21/4" 19'91/4" 9'11/2" 22'61/2" 9'101/4" 9'23/4" 23'2" 17'111/2" 26'31/4" 17'61/4" 30'71/2" 6 28'43/4" 11'10" 19'6¾" 21'-8½" 9'R ळु 굥 4'-10³/₄' 9'R (3')// 8'-44' 9'R 3' 11<u>1</u> 10'-8<u>1</u>' $35.9\frac{1}{4}$ 78'-6" 9'R 9'R 9'R σ 8'R STEP (optional) -2 9'R PANELS -1 BRACE -3 5° WEDGES +1 8'R STEP * = 9'RR ▲ = 5° WEDGE PAD 8' STEP QTY PART BILL OF MATERIALS **G** |HP259LL| 9'R PANEL (LIGHT) HP259 HP204A | 4' PANEL (A/G) HP204 4' PANEL HP226 | 5° WEDGE HP225 | (9'R) 3' ROMAN INSERT HP216 | 1'8" SPECIAL PANEL 35'91/4" 4'8" 3'4" 9'R9'RR ᅘ ą 9'R PANEL DESCRIPTION S U 21'81/2" 11'91/4" 8'111% 15'2" 4 ರಾ PERIMETER -G---I-OVERDIG DETAIL *NOTE: REFER TO INSTALLATION MANUAL FOR MORE INFO. CONCRETE BOND BEAM 6" TO 8" DEEP 93'7" APPROX 4" DEEP BRACE -J--K--It is your responsibility to ensure the safety package provided is delivered to the pool owner and that the "NO DIVING" labels are properly installed. ATTENTION DEALER/BUILDER: NO DIVING WARNING RE-CUT PANEL LEGEND NO DIVING SHALLOW WATER SHALLOW WATER INJURY 3/8" REBAR WHERE NEEDED AROUND PERIMETER OF BOND BEAM SUGGESTED LABEL LOCATIONS ARE SPECIFIED IN THE COPING LAYOUT 'NO DIVING' WARNING LABELS MUST BE ACCORDING NSPI SPECIFICATIONS INSTALLED IN NO DIVING AREAS SQ. FOOTAGE HSH --- 2' OVERDIG ---GALLONS AQUAGENIE 2' VERMICULITE OR SAND BOTTOM BENCHMARK VINYL LINE 19,210 776

uvurment ID: HF5100, Hydra Standard Panel Layout Drawing Rev Date: 1216/2005 Rev Level⁻ A

GENERAL NOTES

. The ideal water level should be to the middle of the skimmer opening(s).

Soil to have minimum bearing capacity of 2000 P.S.F.
 Locate top of pool at least 6" above surrounding land elevation.
 See "Panel Shelf Death" for excavation around pool.
 See "Overdig Detail" for excavation around pool.

EXCAVATION NOTES

Rough excavation should be 2" deeper in each instance.

The dealer or contractor who sells or installs your pool is an independant contractor and is not an

THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY.

ADDITIONAL NOTES

construction. Proper installation is the responsibility of the dealer/builder/contractor. only to normal ground conditions. There may be additional precautions and/or methods of agent of the Manufacturer. The construction methods illustrated here are suggestions and apply

Dimensions are from inside pool panels

ese are finished dimensions ready for the liner.

Copyright © 2012 by Hydra Pools

20931-PWH

JAN 2012 ┃CORNERSTONE┃ 21'8" X 35'9" LAGOON RIGHT