

Parallel-Look Ladder



- Tubing: 1.90" OD
- Wall Thickness: .049"
- Stainless Steel: 304 or 316L Marine Grade* (add -MG to part number)
- Treads: LTDF-101 Plastic (Econoline) or LTDF-103 Stainless Steel (Elite)
- Bends: 6" Radius
- Options: Powder-coating and SealedSteel Salt Friendly available
- Recommended anchors: AS-100B (order separately)
- Recommended escutcheon: EP-100F (order separately)

* Minimum requirement for salt pools is 316L Marine Grade

Econoline	Shipping Wt.	Elite	Shipping Wt.	Description	Length	Width	Height
PLL-12E-2A	22 lbs	PLL-12S-2A	22 lbs	2-step	60"	28"	2"
PLL-12E-3B	24 lbs	PLL-12S-3B	24 lbs	3-step	65"	28"	2"
PLL-12E-4C	28 lbs	PLL-12S-4C	28 lbs	4-step	82"	28"	2"
PLL-12E-5D	31 lbs	PLL-12S-5D	31 lbs	5-step	90"	28"	2"

Notes:

- Frames extend 6½" from the pool wall. Frame is secured to the pool deck with two anchor sockets, 3½" from the pool wall on 20" centers (Elite model) or 19" centers (Econoline model). The lower end of the frame is bent to meet the pool wall and fitted with two white rubber bumpers (WRB-100A).

