

SPECIFICATION

| | | | |
|------------------------------------|--------------------------|---------|---------------------|
| RCA Model | | | RACM5010-6COM |
| Power supply | | Ph-V-Hz | 1Ph, 115V~, 60Hz |
| Cooling | RATED Capacity | Btu/h | 5000 |
| | RATED Input | W | 450 |
| | RATED Current | A | 3.9 |
| Max. input consumption | | W | 540 |
| Max. current | | A | 5.0 |
| Starting current | | A | 19 |
| Refrigerant type (R32) | | g | 175 |
| Refrigerant type (R32) | | ozs | R32/6.17 |
| Design pressure(145psi=1MPa)(L/H) | | psi | 360/915(2.5/6.3MPa) |
| Operation temp | indoor(cooling/heating) | °C | 16-31/--- |
| | | °F | 61°F -88°F |
| | outdoor(cooling/heating) | °C | 18-43/--- |
| | | °F | 64°F -109°F |
| Application area (Cooling EPA) | | sp.ft | 100-150 |
| Dimension(W*D*H) | | mm | 406x386x318 |
| | | in | 15.98x15.2x12.52 |
| Packing (W*D*H) | | mm | 461x428x402 |
| | | in | 18.14x16.85x15.82 |
| Net/Gross weight | | Kg | 16.9/19 |
| | | lbs | 37.26/41.89 |