

(800) 878-5789 • APC-Mfg.com

Submit Form to: orders@anc-mfa.com or (317) 579-2006 fax

STANDARD COVER SYSTEM

Order Form

Submit 1 om to. Graef			1) 313-2000 lax	○ Or	rder	O Quote Only
ORDER INFORMATION	ON		QUID T	O NAME		
Dealer Shire						_
Ioh Name				Address		
PO#				t/Phone#		
			(F	Reauired)		
SHIP TO:		SHIP TO ME				ING ADDRESS?
DistributorHold at DockPreDealerPick UpCo		re-Paid (APC Preferred Carrier)) No (Requ	<u> </u>
_ ,		○ 3rd Party Collect		INSTALLA	TION DATE:	
Other	Oth	er				
JOB SPECIFICATION	NS					
 Under Track Encapsulation Gunite Deck on Deck Inverted Gunite Drilled Choose One: Preship Encapsulation 		○ Manual ————————————————————————————————————		HOUSING TYPE: Recessed APC Polymer Box (free stake) Wood Concrete Other		Deck Mount (TT) ○ Vinyl Bench □ White □ Beige □ Gray ○ Bench Ends Only □ White □ Beige □ Gray
		Choose One: ○ Preship U-Channel ○ Ship U-Channel with System		Choose One:		○ Bench Frame Only
				○ Preship Polymer Box		○ No Bench or Frame
○ Ship Encapsulation with S○ Not Needed	ystem	O Not Needed		○ Ship Polymer Box w/System○ Not Needed		O Split Bench (drawing required)
CONTROLLER: ○ Touch Pad (standard) ○ Keyswitch (LV) ○ 2nd Controller	UNIT SET BACK FROM POOL: Inches Std: 12" / Max: 24"		POOL SIZE: Including Stepsft. Xft. For exterior steps, include drawing	TRACK SPACE: Widthftin. Lengthft.	LID TYPE: ○ Aluminum Lid (Standard) □ 5" Hinge □ 7" Hinge ○ Aluminum Lid Trays Qty: □ MC-0374 (24" x 16" x 1.5" w/strap) □ MC-0509 (24" x 16" x 1.5" w/o strap)	
MOTOR TYPE: MOTOR		<u>:</u> :	FIBERGLASS			
○ Electric□ High Torque		\preceq	POOL MFG MODEL NAME/#:	POOL TYPE:		
= 200 VAO/00112		L		○ Vinyl	○ Adj. Flush Lid Riser □ Needed	
○ Spa (max 10' x 25')○ Hydraulic	Left COVER	BOX Right		○ Fiberglass○ Concrete	○ Stone L	Lid Riser □ Needed er □ 3/8" Riser
LID BRACKET:	FABR	IC COLOR:		DROP TO WATER:	<u> </u>	DDITIONAL MATERIALS:
O HD2: 11"		Navy Blue				○ Lid End Protectors○ Ladder Hinges○ System Bonding Kit○ Rope Reel Protectors
○ Atlas: 12 - 16"	oty Oty OPTIC OAno O1" L	OPTIONS: ○ Anodized L.E. ○ Painted L.E. ○ 1" L.E. ○ Bonding Wire in fabric ○ Loop ○ Comm. Pkg (> 24')		SLACK: " 6" Slack Standard for UT 7" Slack Standard for TT		○ Re-Usable Form - Bullnose○ Re-Usable Form - 90°○ 2nd Cover Pump○ Cover Blast Nozzle
COMMENTS/SPECIAL INSTR	RUCTIONS:		-		(○ Concrete Lid Support Brackets