

# WINDOW AIR CONDITIONERS



**BTUS** 5,000 / 6,000 / 8,000 / 10,000 / 12,000 / 15,000 / 24,000



## 2AW500MSA

- Manual adjustable temperature control
- Slide-out washable filter
- 2-speed rotary dials
- 2-way air direction control
- Window mounting kit included
- ISTA 6A packaging



	2AW500MSA	2AW600DA
<b>UPC</b>	850012484202	850012484141
<b>POWER SUPPLY (V)</b>	115	115
<b>COOLING CAPACITY (BTU)</b>	5,000	6,000
<b>COVERAGE (SQ. FT.)</b>	150	250
<b>CEER</b>	11	11
<b>ENERGY STAR RATED</b>	No	No
<b>FAN SPEEDS (COOL/FAN)</b>	2/2	3/3
<b>AMPS</b>	4.5	5
<b>WATTS</b>	460	490
<b>REMOTE</b>	No	Yes
<b>WINDOW WIDTH (MIN./MAX.) (IN.)</b>	23/34	26/36
<b>WINDOW HEIGHT (MIN.) (IN.)</b>	14½	14½
<b>UNIT DIMENSIONS (W×H×D) (IN.)</b>	16 × 12 × 13½	16 × 12½ × 15¼
<b>PKG. DIMENSIONS (W×H×D) (IN.)</b>	18¼ × 15¼ × 14¾	18¼ × 16 × 17
<b>STUFFING QTY. (20'/40'/40' HQ)</b>	-/-/918	325/675/810
<b>WEIGHT (NET/GROSS) (LBS.)</b>	36/42	40/45
<b>REFRIGERANT</b>	R32	R32
<b>OUTLET CONFIGURATION</b>		



## 2AW600DA

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging








## 2AW8000DA / 3AW10000DA / 3AW12000DA / 2AW15000EA / 2AW18000EA / 2AW24000EA

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging



2AW15000EA,  
2AW18000EA,  
2AW24000EA only.

	2AW8000DA	3AW10000DA	3AW12000DA	2AW15000EA	2AW18000EA	2AW24000EA
<b>UPC</b>	850012484158	850012484172	850012484189	850012484103	850012484110	850012484127
<b>POWER SUPPLY (V)</b>	115	115	115	115	230	230
<b>COOLING CAPACITY (BTU)</b>	8,000	10,000	12,000	15,000	18,000	24,000
<b>COVERAGE (SQ. FT.)</b>	350	450	550	700	1000	1500
<b>CEER</b>	10.9	10.9	10.9	11.8	11.8	10.3
<b>ENERGY STAR RATED</b>	No	No	No			
<b>FAN SPEEDS (COOL/FAN)</b>	3/3	3/3	3/3	3/3	3/3	3/3
<b>AMPS</b>	7.0	8.0	9.5	12.8	9.0	13.0
<b>WATTS</b>	740	850	990	1270	1500	2360
<b>REMOTE</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>WINDOW WIDTH (MIN./MAX.) (IN.)</b>	26/36	26/36	26/36	28/41	28/41	30/41
<b>WINDOW HEIGHT (MIN.) (IN.)</b>	14½	16	16	19	19	19½
<b>UNIT DIMENSIONS (W×H×D) (IN.)</b>	18¾ × 13½ × 15¾	19¾ × 15¼ × 21½	19¾ × 15¼ × 21½	23¾ × 20 × 25½	23¾ × 20 × 25½	26½ × 18¾ × 27
<b>PKG. DIMENSIONS (W×H×D) (IN.)</b>	21½ × 16 × 17¾	24½ × 18½ × 22¾	24½ × 18½ × 22¾	30½ × 21¼ × 26½	30½ × 21¼ × 26½	31½ × 21¼ × 29¾
<b>STUFFING QTY. (20'/40'/40' HQ)</b>	265/550/656	144/304/380	144/304/380	96/216/268	96/216/268	84/188/233
<b>WEIGHT (NET/GROSS) (LBS.)</b>	48.5/55	61/68	68.5/76	106/117	117/128	130/142
<b>REFRIGERANT</b>	R32	R32	R32	R32	R32	R32
<b>OUTLET CONFIGURATION</b>	